



Product Schedule 40 Plain End Cellular Core ABS DWV Pipe

Project Information

Job Name: _____	Date Submitted: _____
Location: _____	Submitted by: _____
Engineer: _____	Approved by: _____
Contractor: _____	Manufacturer's Rep: _____

Application Information

For use for DWV applications only.

Technical Data

Materials

Acrylonitrile Butadiene Styrene

Pressure Ratings

DWV Only

Temperature Ratings

Max Operating Temperature: 150°F

Codes

Universal Plumbing Code (UPC)

National Plumbing Code of Canada

Standards

ASTM F628

Listings

IAPMO 10434

Dimensional Information

	Pipe Size	Part Number	Dimensions			Pieces Per Lift
			O.D. (in)	Nom. Pipe Size (in)	Weight (lbs)	
	1-1/2"×10'	29-1510	1.900	1-1/2	2.70	259
	1-1/2"×20'	29-1520	1.900	1-1/2	5.40	259
	2"×10'	29-210	2.375	2	3.70	167
	2"×20'	29-220	2.375	2	7.40	167
	3"×10'	29-310	3.5	3	7.45	75
	3"×20'	29-320	3.5	3	14.90	75
	4"×10'	29-410	4.5	4	10.71	48
	4"×20'	29-420	4.5	4	21.42	48
	6"×10'	29-610	6.625	6	18.78	40
	6"×20'	29-620	6.625	6	37.56	40

