

# PVC IPS Solvent Weld Pressure Pipe - East

## Conforms to ASTM D 2241

- Certified to requirements of ANSI/NSF 14
- Product manufactured with one integral solvent-weld bell per length
- Standard overall pipe length is 20-feet
- Standard color is white



Trade Size	Part Number	Dimensions (in)		Minimum Wall Thickness (in)	Approximate Weight per 100' (lbs)	Crate Quantity (ft)
		Avg OD	Approx ID			
<b>SDR 26 - Pressure Rating 160 psi</b>						
1¼	5112520	1.660	1.52	0.064	21	4,400
1½	5115020	1.900	1.75	0.073	27	3,600
2	5120020	2.375	2.18	0.091	42	2,100
2½	5125020	2.875	2.64	0.110	62	1,460
3	5130020	3.500	3.21	0.135	92	1,500
4	5140020	4.500	4.13	0.173	152	1,140
6	5160020	6.625	6.08	0.255	330	520
<b>SDR 21 - Pressure Rating 200 psi</b>						
¾	5207520	1.050	0.92	0.060	12	8,000
1	5210020	1.315	1.18	0.063	16	5,600
1¼	5212520	1.660	1.49	0.079	25	4,400
1½	5215020	1.900	1.71	0.090	33	3,600
2	5220020	2.375	2.14	0.113	52	2,100
2½	5225020	2.875	2.58	0.137	76	1,460
3	5230020	3.500	3.15	0.167	113	1,500
4	5240020	4.500	4.05	0.214	186	1,140
6	5260020	6.625	5.96	0.316	405	520
<b>SDR 13.5 - Pressure Rating 315 psi</b>						
½	5305020	0.840	0.71	0.062	10	7,200