

PVC DR 35 Solvent Weld Sewer Pipe - East

Conforms to ASTM D 3034

- Available in solid-wall or with perforations
- Perforated sewer pipe meets the requirements of ASTM D 3034 prior to perforation
- Perforated pipe is manufactured with 5/8 -inch holes, 5-inches on center and is available in 2-hole and 3-hole configurations
- Product manufactured with one integral solvent-weld bell per length
- Standard overall pipe length is 20-feet or 10-feet
- Color of pipe is white or green

Trade Size	Part Number		Perf Pattern	Color	Dimensions (in)		Minimum Wall Thickness (in)	Approximate Weight per 100' (lbs)	Crate Quantity (ft)
	Solid	Perforated			Avg OD	Approx ID			
4 x 10'	3040010	3040010FH	4-8	White	4.215	3.96	0.120	104	630
4 x 10'	3040010	3040010FH468	4-6-8	White	4.215	3.96	0.120	104	630
4 x 20'	3040020	-	-	White	4.215	3.96	0.120	104	1,260
6 x 10'	3060010	3060010FH	4-8	White	6.275	5.89	0.180	236	260
6 x 10'	3060010	3060010FH468	4-6-8	White	6.275	5.89	0.180	236	260
6 x 20'	3060020	-	-	White	6.275	5.89	0.180	236	520
8 x 10'	3080010	-	-	White	8.400	7.89	0.240	429	140
4 x 10'	3040010GRN	3040010FHGRN	4-8	Green	4.215	3.96	0.120	104	630
4 x 10'	3040010GRN	3040010FH468GRN	4-6-8	Green	4.215	3.96	0.120	104	630
4 x 20'	3040020GRN	-	-	Green	4.215	3.96	0.120	104	1,260
6 x 10'	3060010GRN	3060010FHGRN	4-8	Green	6.275	5.89	0.180	236	260
6 x 10'	3060010GRN	3060010FH468GRN	4-6-8	Green	6.275	5.89	0.180	236	260
6 x 20'	3060020GRN	-	-	Green	6.275	5.89	0.180	236	520