

PVC IPS Gasketed Pressure Pipe - West

Conforms to ASTM D 2241

- Certified to requirements of ANSI/NSF 61
- Product manufactured with one integral gasketed bell per length
- Each spigot end is beveled to facilitate assembly and reference marked to indicate proper insertion depth
- Pipe is produced in 20-foot laying lengths
- Standard color is white



Trade Size	Part Number	Dimensions (in)		Minimum Wall Thickness (in)	Approximate Weight per 100' (lbs)	Crate Quantity (ft)
		Avg OD	Approx ID			
SDR 26 - Pressure Rating 160 psi						
4	5140020G	4.500	4.13	0.173	156	1,140
5	5150020G	5.563	5.11	0.214	239	760
6	5160020G	6.625	6.08	0.255	339	520
8	5180020G	8.625	7.92	0.332	559	300
10	51100020G	10.750	9.87	0.413	897	240
12	51120020G	12.750	11.71	0.490	1,264	160
SDR 21 - Pressure Rating 200 psi						
4	5240020G	4.500	4.05	0.214	191	1,140
6	5260020G	6.625	5.96	0.316	416	520
8	5280020G	8.625	7.76	0.410	704	300
10	52100020G	10.750	9.65	0.511	1098	240
12	52120020G	12.750	11.44	0.606	1550	160