

H-162



Insert custom dimensions

$1\frac{3}{16}" \times 1\frac{5}{8}"$

12 Gauge Channel

Weight/100 ft. - 135 lbs.

H-162 is a light-duty channel well suited for many applications. This product is commonly used for trapeze to support MEP systems. It is available "slotted" or with several other pre-punched hole and weld configurations.



SPECIFICATIONS

General

H-STRUT® channels are manufactured from high quality, domestically sourced structural steel and roll formed into shape. These products comply with MFMA-4 standards, and beam and column load tables are calculated in accordance with the ANSI North American Specification for the Design of Cold-Formed Steel Structural Members, 2016 Edition.

Length Information

H-Strut channels are produced in standard 10' and 20' lengths with a tolerance of $\pm\frac{1}{8}"$. Other lengths are available upon request.

Loading Data

1. Load capacities in this section include a safety factor (to the yield strength) of 1.68 for beam loads and 1.80 for column loads.
2. When calculating load at center of span, multiply load from table 0.5 and deflection by 0.8.
3. When calculating beam and column loads for aluminum, multiply by 33%.

Material

H-Strut channels are produced from prime structural metals covered by the following specifications.

(See the technical section for additional information.)

- Aluminum (Type 6063-T6) ASTM B221
- Plain Steel ASTM A1011 SS Grade 33
- Pre-Galvanized Steel ASTM A653 SS Grade 33, G90
- Stainless Steel (Type 304 & 316L) ASTM A240

Other materials and specifications are available upon request.

Finishes

H-Strut is available in powder-coated and zinc trivalent. Other finishes are available upon request.

- Hot-Dip Galvanized ASTM A123
- Zinc Trivalent Chromium (ZTC) ASTM B633
- Powder-Coated




H-162

Section Properties

Catalog No.	Wt. lbs/ft	Area in ²	X-X Axis			Y-Y Axis			dy in
			I in ⁴	S in ³	r in	I in ⁴	S in ³	r in	
H-162	1.37	0.387	0.032	0.068	0.288	0.14	0.172	0.601	0.337

I = Moment of Inertia S = Section Modulus r = Radius of Gyration



Span or Unbraced Height	Static Beam Loading (X-X Axis)					Weight of Channel	Column Loading Data				Unbraced Length Factor	
	Max Allowed Uniform Load	Deflection at Uniform Load	Uniform Load at Deflection				Max Allowed Load at Slot Face	Max Column Load Applied at C.G.				
			Span/180	Span/240	Span/360			k=0.65	k=0.80	k=1.0		k=1.2
in	lbs	in	lbs	lbs	lbs	lbs	lbs	lbs	lbs	lbs	lbs	
24	560	0.11	560	520	340	2.7	2,370	7,580	7,170	6,680	6,250	1.00
36	370	0.24	310	230	150	4.1	2,250	6,740	6,250	5,670	5,110	1.00
48	280	0.43	170	130	90	5.5	2,150	6,050	5,480	4,740	4,010	1.00
60	220	0.65	110	80	60	6.9	2,000	5,430	4,740	**	**	1.00
72	180	0.92	80	60	40	8.2	1,840	4,830	4,010	**	**	1.00
84	160	1.30	60	40	30	9.6	**	4,230	**	**	**	0.98
96	140	1.70	40	30	20	11.0	**	**	**	**	**	0.95
108	120	2.08	30	30	20	12.4	**	**	**	**	**	0.91
120	110	2.61	30	20	NR	13.7	**	**	**	**	**	0.88
144	90	3.70	20	NR	NR	16.5	**	**	**	**	**	0.82
168	80	5.22	NR	NR	NR	19.2	**	**	**	**	**	0.76
192	70	6.81	NR	NR	NR	22.0	**	**	**	**	**	0.69
216	60	8.32	NR	NR	NR	24.7	**	**	**	**	**	0.63
240	50	9.51	NR	NR	NR	27.5	**	**	**	**	**	0.56

NR indicates not recommended | * indicates uniform load limited by weld shear | ** indicates KL/r > 200

Notes:

- The beam weight must be subtracted from the above capacities to arrive at the net beam capacity.
- Allowable beam loads are based on a uniformly loaded, simply supported beam. For capacities of a beam loaded at midspan at a single point, multiply the beam capacity by 50% and deflection by 80%.
- The above chart shows beam capacities for strut without holes. For strut with holes, multiply by the following:
 - OS by 88%
 - RS (7/16 holes) by 88%
 - OS2.5 by 86%
 - OS3 by 90%
 - KO by 82%
- Refer to the latest Haydon Engineering Catalog for reduction factors for unbraced lengths, or contact us at engineering@haydoncorp.com or 1-800-242-9366.

PROJECT INFORMATION			
Project:		Notes:	
Address:			
Contractor:			
Engineer:	Date:		
APPROVAL			
☐ Approved ☐ Approved as Noted ☐ Not Approved		Signature: _____ Remarks: _____	

1-800-242-9366 | haydoncorp.com | submittal@haydoncorp.com

in © Copyright 2026 by Haydon Corporation. All rights reserved. HC020259 4/2026
All trademarks and service marks denoted with TM, SM, or ® are owned by Haydon Corporation unless otherwise noted

HAYDON